

PAINTCOR

SUPREME QUALITY *Since 1986*

2K WATERPROOFING SYSTEM

Description and Application

SURFACE PREPARATION AND APPLICATION FOR ACRYLATEX 2 COMPONENT NEW FLAT DECK WATERPROOFING (ACRYLATEX AND CEMENT 1:1 VOLUME)

- 1) Ensure flat deck concrete roof is clean, dry and free from crumbly or other unsound areas.
- 2) Apply 1 coat of Paintcor AcrySeal to the entire deck including parapet walls. Allow \pm 1 hour to dry @ 25°C.
- 3) Mix equal parts by volume not by weight (1:1) of AcryLatex and Cement. Mix the slurry well, ensuring no lumps.
- 4) Apply 1 liberal coat of the Latex slurry by brush or roller to the entire deck including parapet walls. Bed an alkali resistant bandage into the wet latex and cement slurry. Apply small sections at a time ensuring that the latex cement mix is still wet when bedding the bandage into it. Allow 2 hours @ 25°C to dry.
- 5) Finally apply a second liberal coat of Acrylatex and Cement slurry to completely cover the bandage. Allow 48 hours to dry.
- 6) Overcoat the completed Acrylatex 2 K system with at least two coats of Paintcor's RuvAcryl, Elegance or Aqua Seal. (Product required dependant on colour and guarantee terms requested).

HINTS, TIPS AND GUARANTEE TERMS

- 1) Bandage the entire roof including to the edge of the parapets.
- 2) Adhere to drying times.
- 3) Finishing the Flat deck in the colour white is recommended to keep temperatures down in the home and it reduces expansion and contraction of the flat deck.
- 4) With the choice of top coats, your deck can be finished in the colour of your choice.

GUARANTEE TERMS

The Flat deck must be inspected annually to insure drainage is open and that there are no structural defects.

The following maintenance must be carried out dependant on the top coat used:

- 1) AquaSeal Top Coat: New coat to be applied every 3 to 4 years after inspection.
- 2) RuvAcryl Top Coat: New coat to be applied every 7 years after inspection.
- 3) Elegance Top Coat: New top coat to be applied every 7 or more years after inspection.

Should these terms not be adhered to the guarantee will become null and void. Guarantee does not cover structural defects.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

