

PAINTCOR

SUPREME QUALITY *Since 1986*

ACRYLATEX

Technical Specifications

Vehicle Type	Pure Acrylic
Solvent	Water
Enviro Rating	VOC \pm 5% less
Dilution / Thinning	High strength: No dilution / Normal rate 1:1 with water
Theoretical Spread Rate	N/A
Apply with	Brush or roller
Drying time	@ 25°C 48 Hours
Wash ability	N/A
Elongation	200% +
Pigment	Non-Pigmented
Solids Volume	\pm 41%
Flexibility	Excellent
Colour	Clear when dry
Finish	N/A
Storage	Cool, dry place
Over coating	Paintcor Acrylic Top coat of your choice
Packaging	1L, 5L, 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	N/A
Freeze Thaw	Pass
Accelerated Stability	N/A
Accelerated Weathering	Excellent
Appearance	Milky Substance

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

