

# PAINTCOR

SUPREME QUALITY *Since 1986*

## ACRYLUNDER

### Description and application

#### CATEGORY

Undercoat

#### DESCRIPTION

Acrylunder Acrylic Undercoat is specifically formulated as a quality first-coat for new cement plaster. Acrylunder has excellent adhesion and filling properties with no added lead and low VOC.

#### FEATURES

- Excellent binding.
- Resistance to Alkali.
- Good hiding power.
- Good film building properties and can be used as a filler coat.

#### SURFACE PREPARATION AND APPLICATION

1. Brush the raw plaster to remove any loose friable particles.  
If the plaster is poor (loose and friable), apply 1 coat of Paintcor AcrySeal Acrylic Sealer and allow to dry.
2. Apply 1 coat of Paintcor's Acrylunder by brush, roller or airless spray. Allow to dry.
3. Apply top coats of your choice.

**Note:** Tinted colours will go darker if water is added to them.

#### CLEANING EQUIPMENT

Clean all equipment with water after use.

#### Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
**RSA**

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

