

# PAINTCOR

SUPREME QUALITY *Since 1986*

## AQUA MATT

### Technical Specifications

Vehicle Type	Modified Acrylic Co-polymer
Solvent	Water
Enviro Rating	VOC 5% less
Dilution / Thinning	Supplied ready for use
Apply with	Brush or Roller
Drying time	1 hour @ 25°C @ ± 150µm film thickness
Wash ability	Good
Elongation	200%
Pigment	Pigmented white
Solids Volume	± 58%
Flexibility	Good
Colour	Off White
Finish	Matt
Storage	Cool, dry place
Over coating	AquaSeal, Elegance (Silk) or RuvAcryl
Packaging	250ml, 500ml, 1L, 5L, 20L
Guarantee	5 or 10 years dependant on top coat used
Conditions of Guarantee	5 Years when over coated with Paintcor AquaSeal. 10 Years when over coated with Paintcor's Elegance silk or RuvAcryl. Annual inspection to be carried out on both systems with cracking repaired if necessary and over coating of AquaSeal before the 5 year period end.
Resistance to Water	Excellent
Resistance to Solvents	Some solvents
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	0.5mm
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass once over coated
Appearance	Viscous White Coating

**Note:** For best performance follow application instructions.

**Paintcor cc**  
Reg No: CK 86/19456/23  
VAT No: 4830119311  
**Members:** G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

