

PAINTCOR

SUPREME QUALITY *Since 1986*

AQUASEAL SATURATOR AND TOP COAT

Description and Application

CATEGORY

Waterproofing and Damp Proofing / Wall Coating

DESCRIPTION

AquaSeal is a seamless, acrylic waterproofing system incorporating a Geo-Fabric non-woven membrane. The system has been designed to provide a highly durable, elastic and attractive system which can be used on varying substrates. AquaSeal is a minimum four coat application.

FEATURES

- Waterproof
- Can take ponding water
- Good U.V. resistance
- Excellent Flexibility
- Available in a standard range of colours
- Supplied in Saturator and top coat (keeps costing reasonable)

SURFACE PREPARATION AND APPLICATION

New slab

Clean surface down to remove all dust and loose, friable material. Ensure the surface is dry. Apply by Brush, Roller or Spray.

1. Apply 1 coat of Paintcor AcrySeal Acrylic Sealer, diluted 1:1 with water to the entire deck and parapet walls. Allow to dry. If you suspect that the deck is damp or still green (wet) then Paintcor's Cementek Sealer must be used in place of AcrySeal Acrylic Sealer. Please see Cementek data sheet. NOTE: If AcrySeal is used as a sealer on damp or green (wet) new flat deck, before waterproofing, blistering of the system may occur after drying.
2. Apply 1 thick coat of AquaSeal Saturator to the sealed deck. Bed the membrane into the still wet AquaSeal Saturator, using our ribbed roller or paint brush with a dabbing action. Apply small areas at a time as it is essential that the AquaSeal Saturator coat is still wet when applying the membrane. Allow the system to dry.
3. Apply 1 or 2 more coats of AquaSeal Saturator to begin to completely seal and cover the membrane. Allow drying between coats.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited



PAINTCOR

SUPREME QUALITY *Since 1986*

4. Finally apply 2 top coats of Paintcor's AquaSeal (Top coat), RuvAcryl or Elegance Silk. Allow to dry between coats. RuvAcryl or Elegance Silk can be supplied in the colour of your choice.

Guarantee Terms and Conditions

- A. If finished in AquaSeal: 5 Years
 1. Roof to be inspected by the applicator once a year before summer.
 2. New Top coats of AquaSeal to be applied after 3 years and thereafter when necessary.
 3. All down pipes are to be kept clean and open.
 4. Periodically clean all debris from the roof.
- B. If finished in RuvAcryl or Elegance Silk: 10 Years
 1. Roof to be inspected by the applicator once a year before summer.
 2. New top coats of RuvAcryl or Elegance to be applied after 5 years and thereafter when necessary.
 3. All down pipes are to be kept clean and open.
 4. Periodically clean all debris from the roof.

NOTE: It is important to inspect your waterproofing system annually for any defects. Failure to adhere to these conditions will void your guarantee.

Cleaning Equipment

Clean all equipment with water immediately after use.
Keep all buckets closed when not in use.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

