

PAINTCOR

SUPREME QUALITY *Since 1986*

ART-FX GLAZE COAT

Description and Application

CATEGORY

Paint Techniques / Wood Treatment / Decoupage Varnish / Chalk-It clear sealer

DESCRIPTION

Water-based, adhesion-promoted varnish based on a pure acrylic polymer for over coating wall murals, paint techniques and decoupage as well as a varnish for wood.

FEATURES

ART-FX Glaze Coat is a clear acrylic varnish designed to be tough and UV resistant. It has excellent adhesion and flow for the protection of special paint or art effects on exterior and interior walls. It can also be used as a varnish for wood, a cover coat over decoupage or as a clear sealer on a Chalk-It project.

SURFACE PREPARATION AND APPLICATION

Art work, Decoupage, Chalk-It

1. Ensure the surface you are going to apply the Glaze Coat to is clean, dry and free of loose particles.
2. Apply a thin coat of ART – FX Glaze Coat by brush, roller or airless spray over the special effect or art piece to be covered. Being a clear coat, if used outside, a new coat should be applied every few years.

Surface Preparation and Application (Wood)

1. Sand wood to a clean smooth finish. Remove all sanding dust.
2. Apply 1 coat of Art-FX Glaze coat to the wood. Allow 1 hour at 25°C to dry.
3. Apply a second coat of Art-FX Glaze coat. Allow to dry. A minimum of two coats are required for exterior use.

Cleaning Equipment

Clean all equipment with water immediately after use.

NOTE: Art-FX Glaze Coat can be supplied in various wood stain colours on request.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

