

PAINTCOR

SUPREME QUALITY *Since 1986*

ART FX – GLAZE COAT

Technical Specifications

Vehicle Type	Pure Acrylic Adhesion Promoted
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution / Thinning	No more than 10% for spraying
Theoretical Spread Rate	± 15m ² per litre
Apply with	Brush, Roller or spray
Drying time	1 hour @ 25°C
Wash ability	Very Good
Elongation	Good
Pigment	N/A
Solids Volume	± 30%
Flexibility	Good
Colour	Transparent when dry
Finish	Semi-gloss
Storage	Cool, dry place
Over coating	N/A
Packaging	1L, 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Good
Resistance to Solvents	Some solvents
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	20µm - 30µm (2 coats)
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Milky White Liquid

Note: *Due to the many available paints on the market, not all paints have been tested as topcoats for compatibility with this primer. Contact our technical department for further advice.*

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

