

# PAINTCOR

SUPREME QUALITY *Since 1986*

## ART FX –SCUMBLE GLAZE

### Technical Specifications

Vehicle Type	Diluent
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution / Thinning	Maximum dilution: 1 part paint to 4 parts ART - FX Scumble Glaze Minimum dilution: 1 part paint to 2 parts ART - FX Scumble Glaze
Theoretical Spread Rate	N/A
Apply with	Brush, Rag, sponge, Roller or spray
Drying time	Touch dry – 1 hour @ 25°C Overcoat – 12 hours @ 25°C
Wash ability	Poor
Elongation	N/A
Pigment	N/A
Solids Volume	± 4%
Flexibility	N/A
Colour	Dries almost transparent
Finish	Paint Technique
Storage	Cool, dry place
Over coating	Paintcor Art – FX Glaze Coat
Packaging	1L, 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Poor
Resistance to Solvents	Poor
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	N/A
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Off-white liquid / Translucent when dry

#### Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

Head office: 1494 Mailship  
street, Laser Park, Honeydew, 2040  
Postal Address: P.O. Box 917,  
Northriding, 2162  
RSA

Email  
sale@paintcor.co.za  
Website  
www.paintcor.co.za

Tel: 011 794 2885  
Fax no: 011 794 6955  
Emergency Numbers  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

