

PAINTCOR

SUPREME QUALITY *Since 1986*

CEMENTEK

Description and Application

CATEGORY

Cement enhancer / Primer / Sealer

DESCRIPTION

Cementek is a clear, low viscosity, pure acrylic solvent based formulation that cures, seals and dust proofs new “green” concrete and old concrete. It protects against UV rays and has a semi-gloss finish. Cementek is used for application to all types of concrete and plaster including concrete flooring and cement screeds, both old and new.

FEATURES

Cementek allows for:

- The curing and sealing of concrete to be accomplished at once.
- The effective trapping of moisture during concrete curing. This will ensure that the concrete reaches its full PMA once cured.
- Hard-wearing of concrete floors. Stops new concrete floors from dusting.
- Allows to paint within 24 hours of plastering, laying of a new flat deck roof or concrete floors.
- Excellent U.V. protection

Cementek can be used:

- To seal bricks, coloured concrete floors and other porous cementitious surfaces.
- As a sealer on damp plaster without a normal 28-day curing period, before painting.
- As a sealer on green flat deck roofing before waterproofing allowing the waterproofing to be applied after 24 hours instead of normal 28-day curing periods.

SURFACE PREPARATION AND APPLICATION

NEW CONCRETE AND PLASTER

1. Concrete must be laid and properly finished.
2. Concrete surface must be damp but not wet (NO marring by foot traffic).
3. Apply 2 coats of Cementek.
4. Allow 2 hours at 25°C to dry between coats.
5. If used on a green flat deck then allow Cementek to cure for 8 hours at 25°C before applying AquaSeal and membrane, AquaMatt or Paintcor 2K waterproofing system.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited



PAINTCOR

SUPREME QUALITY *Since 1986*

OLD CONCRETE

1. Ensure that there are no loose or friable materials on the old surface.
2. Patch and repair the concrete where necessary.
3. Ensure that the old concrete has no sealers or paint on the surface. If sealers or paint are present, they must be removed before the application of Cementek.
4. Apply 2 coats of Cementek to the prepared concrete.
5. Allow 2 hours at 25°C to dry between coats.

Application Method

1. Apply Cementek using a brush, roller or airless spray.

Cleaning Equipment

Clean all equipment with Turpentine immediately after use.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

