

# PAINTCOR

SUPREME QUALITY *Since 1986*

## CEMENTEK

### Technical Specifications

Vehicle Type	Solvent Borne Pure Acrylic
Solvent	HAWS (High Aromatic White Spirits)
Enviro Rating	Flammable 3
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	10 - 15m <sup>2</sup> per litre
Apply with	Brush, Roller or spray
Drying time	2 hours @ 25°C (before over coating and foot traffic) 7 days or less (Hard Cure)
Wash ability	Good
Elongation	N/A
Pigment	Non Pigmented
Solids Volume	± 14%
Flexibility	Good
Colour	Transparent
Finish	Semi-gloss
Storage	Cool, dry place. Keep out of reach of children)
Over coating	Over coat with good quality Acrylic Paint)
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Very Good
Active Ingredient	Pure Acrylic
Additional Amount	N/A
Caution	Flammable (see Material Safety Data Sheet)
Catalyst Ratio	N/A
Recommended Dry Film	20 microns (2 coats)
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Very Good
Appearance	Water clear

**Paintcor cc**  
Reg No: CK 86/19456/23  
VAT No: 4830119311  
**Members:** G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

