

# PAINTCOR

SUPREME QUALITY *Since 1986*

## DAMPPRIME

### Description and application

#### CATEGORY

Waterproofing and Damp Proofing / Primer

#### DESCRIPTION

Due to DampPrime's excellent adhesion, rising damp is held back in the surface, (cannot penetrate the primer). DampPrime's formulation contains cement which, with the moisture in the wall and other special ingredients, causes the product to harden to a water tight barrier.

#### SURFACE PREPARATION AND APPLICATION

##### Surface Preparation

1. Remove old paint back to bare plaster.
2. Remove any loose, friable material from plaster.
3. Apply Paintcor Ushevu to algae affected areas, allow to dry, then dry brush. (This will remove any algae, if present). See Ushevu Data sheets.

##### Application Method

Brush, Roller

1. Apply the first coat of Paintcor's DampPrime diluted with Turps by 10% to the raw plaster, covering all affected areas. Allow 24 hours to dry.
2. Repair all cracks and blemishes with Paintcor Flash Patch Exterior crack filler. Smooth off before drying.
3. Now apply a second UNDILUTED coat of DampPrime to the surface. Allow 24 hours to dry.
4. The area can now be overcoated with any of Paintcor's quality wall paints. Should an enamel be required as a top coat, DampPrime must be primed with Paintcor PlasterPrime or AcrylUnder Acrylic Undercoat first.

##### Cleaning equipment

Clean all equipment with Turps immediately after use.

#### Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
**RSA**

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

