

PAINTCOR

SUPREME QUALITY *Since 1986*

DAMPPRIME

Technical Specifications

Vehicle Type	Styrene Co-polymer
Solvent	Turpentine
Enviro Rating	Flammable 3
Dilution / Thinning	10% Turpentine on first coat
Theoretical Spread Rate	8m ² per litre
Apply with	Brush, Roller
Drying time	24 hours
Wash ability	N/A
Elongation	N/A
Pigment	Pigmented
Solids Volume	± 44%
Flexibility	N/A
Colour	White
Finish	Matt
Storage	Cool, dry place. Keep out of reach of children.
Over coating	Top Coat of your choice
Packaging	1L, 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable
Catalyst Ratio	N/A
Recommended Dry Film	40um per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	White Solvent based paint

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

