

PAINTCOR

SUPREME QUALITY *Since 1986*

ESSENCE

Technical Specifications

Vehicle Type	Pure Acrylic
Solvent	Water
Enviro Rating	VOC less than 5%
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	8m ² per litre
	NB: A MINIMUM OF 2 COATS TO BE APPLIED
Apply with	Brush, Roller or Spray
Drying time	@ 25°C ± 30 minutes per coat. Overcoat ± 3 hours
Wash ability	Good
Elongation	Good
Pigment	Pigmented
Solids Volume	N/A
Flexibility	Good
Colour	Colour of your choice
Finish	Mild sheen
Storage	Cool, dry place.
Over coating	N/A
Packaging	1L, 5L and 20L
Guarantee	7 Years
Conditions of Guarantee	Product to be applied to manufacturers specifications. Areas below damp proof course, boundary walls and structural defects are not covered by this guarantee.
Resistance to Water	Good
Resistance to Solvents	N/A
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-toxic, Non-flammable, Low VOC
Catalyst Ratio	N/A
Recommended Dry Film	30um (microns) per coat (Minimum 2 coats)
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Emulsion Paint

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

