

PAINTCOR

SUPREME QUALITY *Since 1986*

ECONOCRYL

Description and Application

CATEGORY

Undercoating / Wall Coating / Ceiling Paint

DESCRIPTION

Econocryl Contractor's Acrylic is an economic product which allows both hiding power and maintenance at a low cost without drying to an under-bound chalking surface. Econocryl is perfect for the lower-budget paint jobs and can be over-coated at a later stage with a higher quality wall coating if required.

FEATURES

Econocryl is beneficial for:

- Being resistant to alkaline and can be used directly on cured plaster.
- Having an ultra-matt finish.
- Being used on ceilings where reflection causes problems.
- Breathable coating

SURFACE PREPARATION AND APPLICATION

1. Remove all loose or friable materials from the surface area.

New Plaster

1. Apply 1 coat of Paintcor AcrySeal diluted 1:1 with water to all new plaster. Allow 20 minutes @25 degrees c to dry.
2. Apply 2 coats of Econocryl. Allow to dry between coats.

Old Plaster

1. Check the adhesion of the existing paint. If it is poor, remove all loose, peeling paint. Apply 1 coat of Paintcor AcrySeal diluted 1:1 with water to all areas where paint has been removed. Allow to dry.
2. If the surface area is powdery, wash to remove all powder before applying one coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water. Allow to dry.
3. Apply 2 coats of Econocryl. Allow to dry between coats.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited



PAINTCOR

SUPREME QUALITY *Since 1986*

4. If the adhesion of the old paint is good, wash walls down to remove all dirt and dust and allow to dry, then apply one or two coats of Paintcor's Econocryl.
5. Clean all equipment with water immediately after use.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040

Postal Address: P.O. Box 917,
Northriding, 2162

RSA

Email

sale@paintcor.co.za

Website

www.paintcor.co.za

Tel: 011 794 2885

Fax no: 011 794 6955

Emergency Numbers

+27(0) 79 526 1565

+27(0) 84 305 5636



SABS
ISO 9001 Accredited

