

# PAINTCOR

SUPREME QUALITY *Since 1986*

## ELEGANCE SILK

### Description and Application

#### CATEGORY

Wall Coating

#### DESCRIPTION

Elegance Silk is a high quality, enviro-friendly exterior wall coating, designed and formulated (to Grade 1 specifications) using quality raw materials to combat South-Africa's extreme climatic conditions. It is also user-friendly (almost zero spatter, low odour and easy to apply). Elegance Silk has an elegant, silk finish.

#### FEATURES

- Resistance to UV (Sun) Easily passes 1 500 hour SABS Test
- Flexibility (can stretch 200%)
- Stain resistant. Now will resist even hydrocarbon staining.
- Mould resistance
- Covers hairline cracks
- Waterproofs vertical surfaces
- Elegance washes easily (dust removed simply by rinsing with a hose pipe).
- Almost zero roller spatter on application.
- Available in most colours
- Can be supplied with addition anti-mould additive (MX Plus) for coastal or high-humidity conditions.
- Elegance Silk can be used over Paintcor Aquamatt or Aquaseal waterproofing systems as a maintenance coat to extend guarantee periods and will allow for a wider choice of colours.
- Adhesion promoted: It can be applied to a whole range of surfaces like:
  - Old enamel – sand first
  - Metal – prime first
  - Glass – clean first
  - Certain plastics – clean first (Garden Furniture)
  - Bathrooms

Elegance is a truly versatile product adhering to most surfaces to which it is applied.

#### SURFACE PREPARATION AND APPLICATION

##### New Plaster

1. Remove all loose friable material.

#### Paintcor cc

Reg No: CK 86/19456/23  
VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

Head office: 1494 Mailship  
street, Laser Park, Honeydew, 2040  
Postal Address: P.O. Box 917,  
Northriding, 2162  
RSA

Email  
sale@paintcor.co.za  
Website  
www.paintcor.co.za

Tel: 011 794 2885  
Fax no: 011 794 6955  
Emergency Numbers  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited



# PAINTCOR

SUPREME QUALITY *Since 1986*

2. If the plaster is porous and/or under bound then apply 1 coat of Paintcor's Acryseal Acrylic Sealer diluted 1:1 with water. Allow to dry, then if necessary, apply 1 coat of Paintcor's Acrylunder and allow to dry.
3. If plaster is of good quality then apply 1 coat of Paintcor's Plaster Prime. Allow to dry followed by 1 coat of Acrylunder if necessary. Allow to dry. (please see note)
4. Finally apply at least 2 coats of Elegance Silk at a spread rate of no more than 10 meters square per litre per coat. Allow to dry between coats.

## Old Plaster

1. Check adhesion of existing paint. (Cross hatch adhesion test). Using a Stanley knife, cut through the paint surface to the substrate vertically and horizontally approximately 3mm apart, creating little squares. If the edges of the squares curl up, and the square can easily be removed, this means the adhesion of the old paint system is failing. If the paint system is failing, remove all old paint back to a sound surface.
2. Apply 1 coat of Paintcor's Acryseal Acrylic Sealer diluted 1:1 with water to all areas to be painted (if old paint system was failing) Allow to dry. Apply 1 coat of Paintcor's Acrylunder( if necessary). Allow to dry.(please see note)
3. If paint system is in good condition, wash down walls to remove dirt and dust. Allow to dry.
4. Finally apply at least two coats of Paintcor's Elegance Silk at a spread rate of no more than 10 square meters per litre per coat. Allow to dry between coats.

## Application Method

Brush, roller or airless spray.

## Cleaning Equipment

Clean all equipment with water immediately after use.

Note: Acrylunder is only necessary after priming or sealing plaster if plaster texture is a problem. Paintcor's Subtex or Rippletex can also be used to correct major plaster texture differences before application of top coats.

### Paintcor cc

Reg No: CK 86/19456/23  
VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

