

PAINTCOR

SUPREME QUALITY *Since 1986*

ELEGANCE SILK

Technical Specifications

Vehicle Type	Pure Acrylic (Adhesion Promoted)
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. rules
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	8 - 10m ² per litre
	NB: A MINIMUM OF 2 COATS TO BE APPLIED
Apply with	Brush, Roller or spray
Drying time	@ 25°C @ ±25 minutes per coat
Wash ability	Excellent
Elongation	200%
Pigment	Pigmented
Solids Volume	N/A
Flexibility	Excellent
Colour	Colours of your choice
Finish	Matt
Storage	Cool, dry place
Over coating	N/A
Packaging	1L, 5L, 20L
Guarantee	10 Years
Conditions of Guarantee	Products to be applied to manufacturer's specifications. Areas below damp proof course, boundary walls and structural defects are not covered by this guarantee.
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	30 micron (min) per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Excellent
Appearance	Emulsion paint

Note: *Elegance is an adhesion promoted product and can be applied to a wide variety of surfaces, including old enamel, certain plastics, glass, etc.*

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

