

# PAINTCOR

SUPREME QUALITY *Since 1986*

## ENDURACOAT

### Technical Specifications

Vehicle Type	Polyurethane Alkyd
Solvent	Turpentine
Enviro Rating	Flammable 3
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	±9m <sup>2</sup> per litre
Apply with	Brush, Roller or spray
Drying time	@ 25°C – 3 hours to touch dry
Wash ability	Excellent
Elongation	N/A
Pigment	Pigmented
Solids Volume	45 - 46%
Flexibility	Fair
Colour	Colour of your choice
Finish	Satin
Storage	Cool, dry place. Keep out of reach of children
Over coating	N/A
Packaging	1L, 5L
Guarantee	7 Years
Conditions of Guarantee	Guaranteed on Interior use only Product to be applied to manufacturers specifications
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data Sheet)
Catalyst Ratio	N/A
Recommended Dry Film	40um (microns)
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Thixotropic Gel

**Note:** *This product is supplied as a gel and should not be thinned for brush or roller application*

**Paintcor cc**  
Reg No: CK 86/19456/23  
VAT No: 4830119311

**Members:** G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

