

PAINTCOR

SUPREME QUALITY *Since 1986*

ENVIROCOAT

Technical Specifications

Vehicle Type	Modified Pure Acrylic Adhesion Promoted
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	±10m ² per litre
Apply with	Brush, Roller or spray
Drying time	@ 25°C ± 20 minutes to touch dry
Wash ability	Excellent
Elongation	200%
Pigment	Pigmented
Solids Volume	35.5 – 36
Flexibility	Excellent
Colour	Colour of your choice
Finish	Medium Gloss
Storage	Cool, dry place.
Over coating	4 hours @ 25°C
Packaging	1L, 5L and 20L
Guarantee	10 Years
Conditions of Guarantee	Product to be applied to manufacturers specifications Areas below damp proof course, boundary walls and defects are not covered by this guarantee
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	30 - 40um per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Excellent
Appearance	Emulsion Paint

Note: Envirocoat is a water based enamel substitute, with no added lead, VOC of 5% or less and almost odour. Suitable for hospitals, children's cots, toys, etc.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

