

# PAINTCOR

SUPREME QUALITY *From 2086*

## FLASHPATCH

### Technical Specifications

Vehicle Type	Modified Acrylic
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution/Thinning	Supplied ready for use
Theoretical Spread Rate	± 4m <sup>2</sup> per litre when used as a skim coat
Apply With	Trowel, scraper
Drying Time	± 6 hours @ 25°C - 5mm thick
Washability	N/A
Elongation	Good
Pigment	N/A
Viscosity at 25°C	Thick paste
Solids Volume	N/A
Flexibility	Good
Colour	Grey white
Finish	Smooth
Storage	Cool, dry place
Overcoating	Undercoat or top coat of your choice
Packaging	250ml, 500ml, 1l, 5l and 20l
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Very Good
Resistance to Solvents	Fair
Specific Gravity	N/A
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	5mm maximum
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Thick white grey paste

*Note: Do not patch more than a 5mm depth at a time.*