

# PAINTCOR

SUPREME QUALITY *Since 1986*

## FLASHSKIM INTERIOR

### Description and Application

#### CATEGORY

Skimming compound

#### DESCRIPTION

FlashSkim is resin-bound plaster skimmer, designed for interior use. Proper application will result in a smooth white finish, optimising the application of top coats.

#### FEATURES

- Dries to a smooth, white, durable finish with good adhesion.
- It can be sanded easily.
- No primer is required before painting.
- FlashSkim is an excellent alternative to gypsum plasters on well plastered walls.
- Supplied ready for use.
- Improves hiding power of applied subsequent coats.

#### SURFACE PREPARATION AND APPLICATION METHOD

##### Skimming, New Plaster

1. Ensure the plastered wall has been floated straight and has cured.
2. Seal the new plaster with Paintcor's Acryseal, diluted 1:1 with water. Allow 30 minutes @ 25°C to dry.
3. Apply a liberal coat of Paintcor's Flashskim to the surface with the edge of a steel trowel, allowing the product to fill in all imperfections.
4. Scrape any excess Flashskim off your steel trowel onto a square trowel, then, using a firm and consistent motion, skim the excess Flashskim off the surface with the steel trowel, leaving a thin, semi-transparent skim coat behind. Scrape off the excess Flashskim from the steel trowel onto the square trowel and repeat the process. This will result in a durable, smooth white surface after drying. Allow up to 30 minutes at 25 degrees to dry before over coating.
5. Sand any ridges or imperfections to a smooth finish. Remove sanding dust.
6. Paintcor's FlashSkim requires no priming before painting. Apply two top coats of your choice. Allow to dry in between coats.

#### CLEANING EQUIPMENT

Clean all equipment immediately after use with water.

#### Paintcor cc

Reg No: CK 86/19456/23  
VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

Head office: 1494 Mailship  
street, Laser Park, Honeydew, 2040  
Postal Address: P.O. Box 917,  
Northriding, 2162  
RSA

Email  
sale@paintcor.co.za  
Website  
www.paintcor.co.za

Tel: 011 794 2885  
Fax no: 011 794 6955  
Emergency Numbers  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

