

PAINTCOR

SUPREME QUALITY *Since 1986*

FLOORCOAT

Technical Specifications

Vehicle Type	Polyurethane Enamel
Solvent	Turpentine
Enviro Rating	Flammable
Dilution / Thinning	See surface preparation and application
Theoretical Spread Rate	15m ² per litre per coat
Apply with	Brush, Roller or Spray
Drying time	Touch dry in 2 hours @ 25°C
Wash ability	Excellent
Elongation	N/A
Pigment	Pigmented
Solids Volume	± 47%
Flexibility	Low
Colour	Paintcor's standard floor colours
Finish	Satin
Storage	Cool, dry place.
Over coating	N/A
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable
Catalyst Ratio	N/A
Recommended Dry Film	30 - 40 µm per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Alkyd Paint

Note: Apply thin coats.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

