

PAINTCOR

SUPREME QUALITY *From 2086*

KLINKASEAL

Safety Data Sheet

Paintcor cc

P. O. Box 917
Northriding
2162
Tel: (011) 794-2885
Fax: (011) 794-6955

1494 Mailship Street
Laser Park
Honeydew, RSA, 2040
Email: sales@paintcor.co.za
Emergency: (+27) 079 526 1565
(+27) 084 305 5636

1. Product Identification

Product Name KLINKASEAL
Product Code KLI
CAS Name and Number Not available (mixture)
Product Description Alkyd silicone resin in solvent for use on masonry etc.

2. Hazardous Identification

SAPMA Health Hazard Rating 2 Moderate - Minor residual effects could result from accidental exposure despite prompt treatment.

Main Hazard Harmful, flammable.

Flammability Flammable

Chemical Hazard Aliphatic solvents. Keep away from sources of ignition.

Health Effects Eyes: Can cause burning / irritation redness and pain if splashed in eyes.

 Skin: May irritate skin (degrease) with prolonged contact and may lead to dermatitis.

 Ingestion: Harmful. May cause nausea and diarrhoea and damage to the mucous membrane, sore throat, abdominal pains and laboured breathing.

 Inhalation: Adverse health effects from vapours or spray mist in poorly ventilated areas may induce irritation of the nose, throat and respiratory tract. Irritation may cause sore throats, coughing, headaches, dizziness, nausea and loss of consciousness.





3. Composition / Information on Ingredients

This product is a chemical preparation of an Alkylsilicone resin in a petroleum distillate mainly of an aliphatic solvent.

Hazard Components	CAS #	Symbols	Risk Phrases	Safety Phrases	% by WT
Trimethoxy (2,4,4-trimethyl pentyl) silane	34396-03-07	N			> 1%
Di-n-butyltindilaurate	77-58-7	Xn	R20/21/22,R36/38,R48/22,R50/53		< 0.1%
Methanol	67-56-1	Xi	R39/23/24/25	S24/25,S37	< 0.1%
Mineral Spirits	064742-88-7	Xn	R10,R65,R66		> 70%

4. First Aid Measures

Product	In Eyes -	Check for and remove contact lenses. Flush open eyes with water for 15 minutes. Call a physician if necessary.
	Inhalation -	Remove to fresh air and if needed give artificial respiration of oxygen. In severe cases seek medical attention and administer external cardiac massage if necessary.
	On Skin -	Use hand cleaner. Wash skin with soap and water. Remove contaminated clothing. Call a physician if irritation persists.
	Ingestion -	Do not induce vomiting. Give water to drink. If necessary seek medical attention.

Note to a physician: Material if aspirated into lungs may cause chemical pneumonitis. Treat appropriately and monitor for cardiac dysrhythmias.

5. Fire Fighting Measures

Extinguishing Media	Carbon dioxide. Dry powders. Alcohol resistant foam. Fog to cool and control. Do not use water jets.
Specific Hazards	Dry films are capable of burning, giving off oxides of carbon and / or nitrogen. There is a danger of flashbacks if sparks or hot surfaces ignite vapour.
Protective clothing	Use numeral fire fighting equipment and self contained breathing apparatus.

6. Accidental Release Measures

Personal precautions	Eliminate sources of ignition. Wear suitable protective clothing, gloves and eye / face protection. Ensure adequate ventilation ensuring that the OEL is not exceeded or use respiratory protection. Prevent skin and eye contact.
Environmental precautions	Prevent from getting into drains, sewers and waterways. Small spills: Mop up with sand, earth or approved absorbent inert materials and transfer to suitable containers. Large spills: Eliminate all ignition sources. Contain spill by dicing edges with sand, earth or suitable absorbent inert materials (vermiculite). Transfer liquid to suitable container, using spark proof equipment. Keep all spills out of surge lakes, aquifers and any other running water supply. Dispose of in agreement with local regulations.

7. Handling and Storage

Handling precautions	Ensure storage vessels and transfer equipment are earthed. Naked flames and other sources of ignition must not be present. Handle in well ventilated areas. Wear suitable PPE. Avoid contact with skin and eyes.
Storage precautions	Store at ambient temperatures in well ventilated area and prevent any contact from any source of ignition. Keep separate from oxidizers. Keep lids tightly sealed when not in use.
Suitable packaging material	Suitable materials for storage are mild steel, stainless steel and aluminium containers. Plastics and rubber are not recommended, although some polyolefin's can be used for small quantities.

8. Exposure Controls / Personal Protection

SAPMA Rating 2-H-E Hands, Eyes and Respirator
 Engineering control measures No open flames. No smoking. No sparks. Ensure adequate ventilation. If in enclosed area wear NIC approved respirator. Wear appropriate PPE when handling.

Occupational exposure limits

CAS no:	Substance	OEL mg / m ³	ppm	STEL mg / m ³	ppm	TLV
064742-88-7	White spirits					

Personal protection
 Respirator: Use in enclosed areas and must be approved for organic vapours. Normal working conditions should have adequate ventilation.
 Hands: Use barrier cream and wear butyl rubber, PVC, nitrile or other suitable gloves.
 Eyes: Use face shield or goggles / safety glasses with side protection.
 Skin/Body: Use overalls / suitable protective clothing and safety shoes.
 Remove contaminated clothing to avoid skin contact.

Other protection Wash hands before eating and smoking.



9. Physical and chemical properties

Appearance	Clear liquid.
Odour	Characteristic solvent odour.
Solubility in water	Insoluble
Solubility in solvent	Soluble in aliphatic and most aromatic solvents.
Density	0.750 - 0.850 g/l
Flammability	Flammable
Boiling point	> 154 - 205°C (ASTM D 93)
Flash point	Not determined
Melting point	Not determined
Flash point	38°C (ASTM D 93)
Explosive properties	Not explosive
Oxidising properties	Non oxidising
Vapour pressure	Not determined
Decomposition temp	Not determined
Auto ignition temp	Not determined
Viscosity	30 - 40 seconds Ford 4 cup

10. Stability and reactivity

Stability	Stable at ambient temperature.
Conditions to avoid	Exposure to high temperatures or open flames.
Materials to avoid	Strong oxidising agents.
Hazardous decomposition of by-products	Burning will produce dense, acid smoke containing carbon dioxide, carbon monoxide and other noxious fumes.
Hazardous polymerisation	Will not occur.



PAINTCOR

MANUFACTURERS

11. Toxicological Information

Acute toxicity				
CAS no:	Substance	LD50(0) mg / kg	LD50(D) mg / kg	LC50 ml / m3
064742-88-7	Mineral spirits			
Local effects	Eyes:	Burning / irritation, if splashed in eyes.		
	Skin:	Frequent or prolonged contact may irritate and cause dermatitis. May be absorbed with possible systemic effects.		
	Ingestion:	Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchi pneumonia or pulmonary oedema. Low order of toxicity.		
	Inhalation:	High vapour irritates the eyes and the respiratory tract, causing headaches, dizziness, nausea, vertigo and unconsciousness and may have other nervous effects.		
Chronic toxicity	None known			
Carcinogenicity	No evidence of carcinogenic effect			
Mutagenicity	No evidence of mutagenic effect.			
Neuro-toxicity	Mineral spirits is a narcotic and may cause dizziness, nausea, loss of concentration and ultimately loss of consciousness.			
Reproductive hazards	No evidence of reproductive hazards.			

12. Ecological Information

Mobility	Liquid. Spillage may penetrate the soil causing ground water contamination.
Biodegradability	Resin solids are slowly biodegradable. Solvents vaporises.
Bioaccumulation	Solvent can bio-accumulate but with short retention time.
Aquatic toxicity	Resin solids have lower order of toxicity. Solvents is moderately toxic to aquatic life. Large spills may form a film on water surfaces causing physical damage to organisms and impair oxygen transfer.

13. Disposal consideration

Waste disposal	Liquid surplus or waste should be appropriately labelled. Disposal must be in accordance with current national and local regulations. Appropriate disposal is by incineration. Solidified wastes must be land filled in an appropriate H:H or H:h landfill site, but authorization from appropriate sources should be sought.
Packaging disposal	Empty drums should be sent for reconditioning or scrap by a recognised drum reconditioner, appropriately labelled in accordance with national and local regulations. Empty containers pose a fire hazard. Hazard labels should not be removed. Incinerate or treat as for disposal of waste.

14. Transport information

U.N. No.	1223/1866
Substance Identity No.	None
Classification	Flammable
Hazardous warning	UN Packaging group: III / Class: 3.3





PAINTCOR

MANUFACTURERS

15. Regulatory Information

Symbols:	N:	Harmful to environment.
	Xn:	Harmful
	Xi:	Irritant
Hazard Symbols:		Flammable class 3
EC label:		Toluene, 203-625-9
Risk phrases:	R10:	Flammable
	R20/21:	Harmful by inhalation and contact with skin.
	R22:	Harmful if swallowed.
	R36/37/38:	Irritating to eyes, respiratory system and skin.
	R52/53:	Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.
	R65:	Harmful, may cause lung damage if swallowed.
	R66:	Repeated exposure may cause skin dryness or cracking.
Safety phrases:	S2:	Keep out of reach of children
	S16:	Keep away from sources of ignition – No smoking
	S24/25:	Avoid contact with skin and eyes.
	S26:	In case of eye contact, rinse immediately with plenty of water and seek medical advise.
	S29:	Do not empty into drains.
	S36/37/39:	Wear suitable protective clothing, gloves and eye / face protection.
	S38:	In case of insufficient ventilation, wear suitable respiratory equipment.
National / Local regulations:		Refer to Occupational Health and Safety Act (1993). Hazardous Chemical Substance Regulation and General Administrative Regulations.



National/Local Regulations Refer to Occupational Health and Safety Act (1993). Hazardous Chemical Substance Regulation and General Administrative Regulations

16. Other information

Date of Issue: July 2007
Date of last revision: October 2014
Revision No.: 4

Note: The data and recommendations contained herein are based upon data that is considered to be accurate, however, Paintcor cc makes no warranty or guarantee, either expressed or implied, of the accuracy or completeness of this data and recommendations. Paintcor cc advises the user of the product to make their own determinations as to the information suitability and completeness for the particular application.

Abbreviations:

ACGIH: American Conference of Governmental Industrial Hygienists.
OSHA: Occupational Safety and Health Administration
NIOSH: National Institute for Occupational Safety and Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
TWA: Time Weighted Average
STEL: Short Term Exposure Limit
PPE: Personal Protective Equipment.
OEL: Occupational Exposure Limits