

PAINTCOR

SUPREME QUALITY *Since 1986*

LUXURIANCE

Description and Application

CATEGORY

Wall Coating

DESCRIPTION

Luxuriance is an all-purpose exterior and interior acrylic paint. It has been introduced to our range to meet the growing demand for a quality matt finish.

FEATURES

It is made from a combination of non-toxic raw materials.

- It is tough, durable, non-yellowing, odourless and environmentally friendly.
- It has been formulated using fine particle size fillers to achieve the best washability.
- It consists of pure acrylic for excellent weathering.
- It is available in most colours.
- It is an excellent base coat used for various paint techniques, especially when used with Art-FX Scumble Glaze and Glaze Coat.

SURFACE PREPARATION AND APPLICATION

SURFACE PREPARATION - NEW PLASTER

1. Remove all loose and friable materials by brushing the plaster.
2. If the plaster is poor & under bound, apply one coat of AcrySeal acrylic sealer.
3. If the plaster is of good quality, then apply one coat of Paintcor's Plasterprime.

PREVIOUSLY PAINTED PLASTER

1. Check the adhesion of the existing paint by using a cross-hatch adhesion test.
2. Use a Stanley knife to cut through the paint surface. Do this vertically and horizontally to the substrate, approximately 3mm apart, creating little squares.
3. If the edges of the squares curl up, and the square can easily be removed, this means the adhesion of the old paint system is failing.
4. Remove any peeling paint back to original plaster.
5. Apply Acryseal acrylic sealer to plaster.

NEW WOOD TO BE PAINTED USING AN ENVIRONMENTALLY-FRIENDLY SOLUTION

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited



PAINTCOR

SUPREME QUALITY *Since 1986*

1. Sand the wood down to a clean matt finish.
2. Remove any sanding dust.

APPLICATION METHOD - NEW PLASTER

1. Apply one coat of Paintcor's Acrylunder, if Acryseal was used first. If Plasterprime was used first, then it is not necessary to use Acrylunder.
2. Apply two coats of Luxuriance.

PREVIOUSLY PAINTED PLASTER

1. Apply one coat Acrylunder to all exposed, sealed plaster.
2. Apply one or two coats of Luxuriance.

NEW WOOD TO BE PAINTED USING AN ENVIRONMENTALLY FRIENDLY SOLUTION

1. Apply one coat Luxuriance.
2. Allow sufficient time to dry.
3. Apply two acrylic top coats of your choice, such as Elegance or Envirocoat.

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

