

# PAINTCOR

SUPREME QUALITY *From 2086*

## LUXURIANCE

### Safety Data Sheet

#### Paintcor cc

P. O. Box 917  
Northriding  
2162  
Tel: (011) 794-2885  
Fax: (011) 794-6955

1494 Mailship Street  
Laser Park  
Honeydew, RSA, 2040  
Email: sales@paintcor.co.za  
Emergency: (+27) 079 526 1565  
(+27) 084 305 5636

#### Product Identification

Product Name LUXURIANCE  
Product Code LUX  
CAS Name and Number Not available (mixture)  
Product Description Water based plasticiser-free aqueous dispersion based on styrene and acrylic acid esters for use on masonry substrates.

#### 2. Hazard Identification

SAPMA Health Hazard Rating 3 Slight - Minor residual effects could result from accidental exposure if no treatment is applied.

Main Hazard Irritation on eye contact.  
Flammability Non-Flammable  
Chemical Hazard Alkaline Product  
Health Effects  
Eyes: Can cause burning / irritation if splashed in eyes.  
Skin: May irritate skin with prolonged contact.  
Ingestion: May cause nausea and diarrhoea and damage to the mucous membrane.  
Inhalation: Adverse health effects from vapours or spray mist in poorly ventilated areas may induce irritation of the nose, throat and respiratory tract. Irritation may cause headaches and nausea.



#### 3. Composition / Information on Ingredients

This product is a chemical preparation of water based pure Acrylic acid esters polymer, inert fillers and pigments.

Hazard Components	CAS #	OSHA PEL	ACHIG	TWA Limits	% by WT
Ammonia	1336-21-6	35 ppm	25 ppm		< 0.5
Acrylic polymer	Not hazardous				
Water	7732-18-5				<50



#### 4. First Aid Measures

Product In Eyes - Flush open eyes with water for 15 minutes. Call a physician if necessary.  
Inhalation - Remove to fresh air and if needed give artificial respiration of oxygen.  
On Skin - Remove contaminated clothing. Wash skin with soap and water. Call a physician if irritation persists.  
Ingestion - Do not induce vomiting. Give water to drink. If necessary seek medical attention.

#### 5. Fire Fighting Measures

Extinguishing Media Water, foam, carbon dioxide, sand, etc. Product is non-flammable and will not support combustion.  
Specific Hazards May spatter if temperature exceeds boiling point. Paint films are capable of burning, giving off oxides of carbon / nitrogen.  
Protective clothing Use numeral fire fighting equipment and self contained breathing apparatus.

#### 6. Accidental Release Measures


Personal precautions Wear suitable protective clothing, gloves and eye/face protection. Ensure adequate ventilation. Slippery conditions.  
Environmental precautions Prevent large quantities getting into waterways.  
Small spills: Mop up and flush remainder away with water.  
Large spills: Contain spill by dicing edges with absorbent inert materials. Transfer liquid to container. Keep all spills out of surge lakes, aquifers and any other running water supply. Dispose of in agreement with local regulations.

#### 7. Handling and Storage

Handling precautions No special precautions. Normal handling care and PPE.  
Storage precautions Should be kept away from freezing temperatures. Avoid contact with micro-organisms. Keep container tightly sealed when not in use. Keep out of the sun and do not store lower than 5°C.  
Suitable packaging material Polyethylene buckets.

#### 8. Exposure Controls / Personal Protection

SAPMA Rating 3-H-C Hands and Eyes  
Engineering control measures Ensure adequate ventilation. If in enclosed area wear NIC approved respirator.  
Occupational exposure limits None known  
Personal protection  
Respirator: Not required for normal use.  
Hands: No protection required for normal use. PVC gloves.  
Eyes: Not required for normal use. Safety goggles.  
Skin/Body: Use overalls and safety shoes.  
Other protection Wash hands before eating and smoking.





# PAINTCOR

MANUFACTURERS

## 9. Physical and chemical properties

Appearance	Milky to white viscous liquid. Any colour when tinted.
Odour	Slight ammonia and acrylic smell.
PH	8.00 - 9.5
Solubility in water	Miscible
Density	1300 - 1480 g/l
Flammability	Non-flammable
Boiling point	100°C
Flash point	Not determined
Explosive properties	Not determined
Oxidising properties	None known
Decomposition temp	Not determined
Auto ignition temp	Not determined
VOC (g/l)	< 50

## 10. Stability and reactivity

Stability	Stable at ambient temperature.
Conditions to avoid	Exposure to air will form skins on top of liquid.
Materials to avoid	Organic solvents, acid, alkali.
Hazardous decomposition of by-products	None known
Hazardous polymerisation	Will not occur.

## 11. Toxicological information

Acute toxicity	Oral toxicity (LD 50) > 5000 mg/kg
Local effects	Eyes: Burning/irritation, if splashed in eyes. Skin: Irritation/drying with prolonged contact. Ingestion: Nausea, diarrhoea and mucous damage may occur. Inhalation: Light headaches and possible irritation to the mucous membranes.
Chronic toxicity	None known
Carcinogenicity	None known
Mutagenicity	None known
Reproductive hazards	None known

## 12. Ecological information

Biodegradability	Liquid evaporates and solids are slowly biodegradable.
Bioaccumulation	Unlikely to accumulate in the aquatic environment.
Aquatic toxicity - Fish	(LD 50) > 500 mg/l
Aquatic toxicity - Algae	(LC O) approximately 1000mg/l

## 13. Disposal consideration

Waste disposal	Use landfill or incinerate. Obey all local, state and federal laws and regulations. Dispose off all waste directed by these agencies. Do not mix with other chemical waste. Small spills can be diluted and washed into sewers.
Packaging disposal	Drain well and rinse thoroughly before recycling.

## 14. Transport information

U.N. No.	
Substance Identity No.	None
Classification	
Hazardous warning	Not classified as dangerous for transportation by road, rail, sea or air.



# PAINTCOR

MANUFACTURERS

## 15. Regulatory Information

EEC Hazard Classification	Not classified as dangerous.
Hazard symbols	Xi Irritant
Risk phrases	R43: May cause sensitisation by skin contact.
Safety phrases	S2: Keep out of reach of children S24/25 Avoid contact with skin and eyes. If swallowed, do not induce vomiting. Seek medical advice promptly. S28: After contact with skin, wash immediately with plenty of soap and water. If swallowed, do not induce vomiting. Seek medical advice promptly.
National/Local Regulations Contains	None Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 55965-84-9



## 16. Other information

Date of Issue: June 2007  
Date of last revision: October 2014  
Revision No.: 3

**Note:** The data and recommendations contained herein are based upon data that is considered to be accurate, however, Paintcor cc makes no warranty or guarantee, either expressed or implied, of the accuracy or completeness of this data and recommendations. Paintcor cc advises the user of the product to make their own determinations as to the information suitability and completeness for the particular application.

### Abbreviations:

ACGIH: American Conference of Governmental Industrial Hygienists.  
OSHA: Occupational Safety and Health Administration  
NIOSH: National Institute for Occupational Safety and Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
TWA: Time Weighted Average  
STEL: Short Term Exposure Limit  
PPE: Personal Protective Equipment.  
OEL Occupational Exposure Limits