

PAINTCOR

SUPREME QUALITY *Since 1986*

PALLETGUARD

Description and Application

CATEGORY

Wood Paint

DESCRIPTION

PalletGuard is a high-quality, enviro-friendly exterior wooden pallet coating, designed and formulated using quality raw materials to combat South Africa's extreme climatic conditions. As well as being user-friendly (almost zero spatter, low odour, easy to apply), Pallet Guard seals the wood it is applied to, coating the wood with a waterproof, hard wearing decorative and protective finish. Pallet Guard's formulation is very specific. It conforms to EURO Standards on VOC (Volatile Organic Content), which is less than 5% with no toxic pigments or materials being used. Should a painted pallet be burned the only smoke emission will be carbon dioxide. PalletGuard is also hard wearing (reduces pallet damage) yet is still very flexible (more than 200%), which allows the product to move with the expansion and contraction of the wood. Pallet Guard will stop fungal growth on the wood with excellent U.V. protection (tested to 10 years). Combine all these properties and you have a product that can effectively double the life span of wooden pallets. PalletGuard can, on request, be made in almost any colour. Pallets can therefore be branded in corporate colours or by product, etc.

FEATURES

Resistance to UV (Sun) passes 1500 hour test

200% flexibility (can stretch 200%) or more

Stain resistant. Now will resist even hydrocarbon staining.

Mould resistant

Waterproofs

Pallet Guard washes easily (dust removed simply by rinsing with a hose pipe).

Adhesion promoted: Can be applied to whole range of surfaces besides wood.

SURFACE PREPARATION AND APPLICATION

NEW WOOD

1. Ensure wood is clean and dry.
2. Coat all sides of the wood with 2 coats Pallet Guard, ensure all joints and nail heads are sealed. Apply more coats to joints and nail heads to seal them if necessary).
3. Allow to dry between coats.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited



PAINTCOR

SUPREME QUALITY *Since 1986*

OLD WOOD

1. Clean wood and poison fungus (fungus can be destroyed using Paintcor's Ushevu diluted 1 litre to 19 litres water or with undiluted household bleach). Allow to dry. (See Ushevu data sheet for use).
2. Coat all sides of the wood with 2 coats of Pallet Guard. Ensure all joints and nail heads are sealed. (Apply more coats to joints and nail heads to seal them if necessary). Allow to dry between coats.

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

