

PAINTCOR

SUPREME QUALITY *Since 1986*

PLASTERBOND

Description and application

CATEGORY

Primer / Cement Enhancer

DESCRIPTION

PlasterBond is a specially formulated latex which has been developed to promote the adhesion between new plaster and the surface to which the plaster is being applied.

FEATURES

-PlasterBond is Alkali-resistant

SURFACE PREPARATION AND APPLICATION

1. Prepare the surface for re-plastering.
2. Remove all dirt and dust from the surface to be plastered.
3. Ensure the surface is dry.
4. Apply 1 coat of Paintcor's PlasterBond.
5. Allow sufficient time to dry. The product will turn clear on drying.
6. While PlasterBond is still tacky, (just after drying) apply the new plaster.

CLEANING EQUIPMENT

Clean all equipment with water after use.

Note: PlasterBond can be added to cement mixtures to improve their properties (adhesion, water resistance and strength)

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

