

# PAINTCOR

SUPREME QUALITY *Since 1986*

## RHINOSEAL

### Description and Application

#### CATEGORY

Primer / Sealer / Bonding Liquid

#### DESCRIPTION

Rhino Seal is a fine particle size water borne acrylic bonding liquid, specifically designed to penetrate deeply into hard wall surfaces. It is therefore ideally suited for priming gypsum plaster finishes, old chalking paint, new precast concrete or any absorbent new surface before painting. RhinoSeal has excellent alkali and efflorescence resistance and has been tested to penetrate  $\pm 120\mu\text{m}$  into chalking material in one coat with complete binding of the loose friable material to the underlying surface on drying.

#### FEATURES

- Water-borne
- Fine Particle size
- Low odour
- Alkali resistant
- Fast drying

#### SURFACE PREPARATION AND APPLICATION

**For chalking surfaces e.g. poor gypsum plaster, economic paint, White Wash etc.**

1. Ensure surface is dry and free of dust, oil and grease.
2. Treat for algae if necessary with Paintcor Ushevu Algae Killer. (See data sheet)
3. Apply 1 coat of Paintcor's RhinoSeal to the chalking gypsum plaster or old chalking paint. Allow to dry. (Approx. 3hours).
4. After drying, check that the RhinoSeal has penetrated and bound up the surface applied to. If there is still chalk evident on the gypsum plaster or old chalking paint, a second coat of RhinoSeal must be applied.
5. Finally apply 2 top coats of your choice. Allow to dry between coats. (Conventional or textured undercoats may be applied before top coats to correct substrate imperfections).

#### Paintcor cc

Reg No: CK 86/19456/23  
VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



VERY LOW  
VOC

**SABS**  
ISO 9001 Accredited



# PAINTCOR

SUPREME QUALITY *Since 1986*

## APPLICATION METHOD

Brush, roller or spray

## CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

**NOTE:** It is very important to check that the surface treated with RhinoSeal is properly bound before painting. Excessively thick layers of chalking material may not be completely penetrated by RhinoSeal. Check for complete penetration of the substrate before painting. Painting on a poorly or incorrectly primed surface will FAIL. If in doubt please call our Technical Support Desk on (011) 794-4599 / (011) 794-2885 during office hours.

### Paintcor cc

Reg No: CK 86/19456/23  
VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

