

PAINTCOR

SUPREME QUALITY *Since 1986*

RHINOSEAL

Technical Specifications

Vehicle Type	Water Borne Acrylic
Solvent	Water
Enviro Rating	Non-Flammable
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	15 - 20m ² per litre
Apply with	Brush, Roller or spray
Drying time	Allow 1 hour @ 25°C to dry before over coating (Summer)
Wash ability	N/A
Elongation	N/A
Pigment	Non-Pigmented
Solids Volume	N/A
Flexibility	N/A
Colour	Transparent when dry
Finish	N/A
Storage	Cool, dry place. Keep out of reach of children.
Over coating	Top Coat of your choice
Packaging	1L, 5L, 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Good
Resistance to Solvents	N/A
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Keep out of reach of children.
Catalyst Ratio	N/A
Recommended Dry Film	N/A
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	White liquid

Note: RhinoSeal can be used on polystyrene products. Longer drying times are necessary in cold condition.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

