

PAINTCOR

SUPREME QUALITY *Since 1986*

SEALERMIX

Description and Application

CATEGORY

Undercoat/Sealer

DESCRIPTION

Sealermix is a pigmented, alkali resistant plaster-sealer specially designed for scratch plaster but can be used on any new plaster.

FEATURES

- It reduces the high absorption of paint on scratch plaster.
- Good alkali resistance.
- It has excellent binding power.
- It improves the quality of the plaster and the paint system.
- It is slightly pigmented to assist with the hiding power of subsequent coats.
- It can be applied to all types of plaster, cement or concrete.

SURFACE PREPARATION AND APPLICATION

1. Brush the scratch or normal plaster to remove all loose and friable materials.
2. Apply one liberal coat of Sealermix. Allow sufficient time to dry.
3. Apply one coat of Paintcor's Acrylunder acrylic undercoat. Allow sufficient time to dry. Undercoat is only necessary to obtain smoother finished on new plaster.
5. Apply top coats of your choice. Allow to dry between coats.

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

