

PAINTCOR

SUPREME QUALITY *Since 1986*

SEALERMIX

Technical Specifications

Vehicle Type	Modified Acrylic
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. rules
Dilution / Thinning	This product is NOT to be thinned
Theoretical Spread Rate	±8m ² per litre
Apply with	Brush, Roller or Spray
Drying time	@ 25°C ±20 minutes. Allow ±45 minutes before over coating.
Wash ability	N/A
Elongation	OK
Pigment	Pigmented
Solids Volume	N/A
Flexibility	Good
Colour	Can be tinted
Finish	Matt
Storage	Cool, dry place
Over coating	Top coat of your choice
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Good
Resistance to Solvents	Fair
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	N/A
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	White Emulsion Sealer

Note: Spread rates will vary according to porosity of the plaster.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

