

PAINTCOR

SUPREME QUALITY *Since 1986*

SUBTEX

Description and Application

CATEGORY

Undercoat

DESCRIPTION

Subtex has been specially formulated to correct texture differences on new one coat cement plaster. It has been designed to be cost effective, alkaline resistant and can be applied with either sheepskin roller to correct texture difference, or with a ripple roller to give a smooth low-relief ripple. Subtex will cover plaster in one coat when used with a sponged ripple roller. After application of Subtex, top coats of your choice can be applied.

FEATURES

- It is cost effective.
- It has a high binding power and excellent hiding power.
- It is alkaline resistant.
- It has the ability to cover texture differences in new plaster, preventing a patchy finish.
- It is also an Undercoat.

SURFACE PREPARATION AND APPLICATION

NEW ONE-COAT WOOD FLOATED PLASTER

1. Remove all loose or friable materials from the plaster by dry brushing.
2. Seal the plaster with 1 coat of Paintcor's Acryseal acrylic sealer, diluted 1:1 with water. Allow sufficient time to dry.

NOTE: Always seal new plaster with Acryseal when applying Subtex with a ripple roller.

3. Apply one coat of Subtex with a sheepskin roller to correct plaster texture

OR

Apply one coat of Subtex with a ripple roller (sponge roller) to cover scarring and texture differences.

4. Finally apply top coats of your choice. Allow to dry between coats.

Note: Applying textured coatings with a sponge roller requires experienced applicators. Please call us for training if required.

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

