

PAINTCOR

SUPREME QUALITY *Since 1986*

TRI-3 SILVER ALUMINIUM (NON LEAFING)

Technical Specifications

Vehicle Type	Modified Pure Acrylic
Solvent	Water
Enviro Rating	Conforms to EU 2010 C.O.C. rules
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	10 - 12m ² per litre per coat
Apply with	Sponge brush, spray, brush or roller
Drying time	@ 25°C – 2 hours per coat
Wash ability	Excellent
Elongation	200%
Pigment	Silver Aluminium (Non leafing)
Solids Volume	± 32%
Flexibility	Excellent
Colour	Silver Aluminium
Finish	Silk
Storage	Cool, dry place
Over coating	Flexible top coats
Packaging	1L + 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	30 micron per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Excellent
Appearance	Silver Emulsion Paint

Note: TRI-3 Silver Aluminium is an adhesion promoted product and can be applied to a wide variety of surfaces, including old enamel, certain plastics, glass, etc.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



VERY LOW
VOC

SABS
ISO 9001 Accredited

