

# PAINTCOR

SUPREME QUALITY *Since 1986*

## UNISUB

### Technical Specifications

Vehicle Type	Medium Oil Alkyd
Solvent	Turpentine
Enviro Rating	Flammable
Dilution / Thinning	Turpentine
Theoretical Spread Rate	10m <sup>2</sup> per litre
Apply with	Brush, Roller or Spray
Drying time	Surface Dry: 1 hour. Hard Dry: 5 hours
Wash ability	N/A
Elongation	ok
Pigment	Pigmented
Solids Volume	39
Flexibility	N/A
Colour	White
Finish	Matt
Storage	Cool, dry place. Keep out of reach of children.
Over coating	Top coat of your choice
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Good
Resistance to Solvents	Fair
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	30 microns per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	White Alkyd Paint

**Paintcor cc**  
Reg No: CK 86/19456/23  
VAT No: 4830119311

**Members:** G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

