

PAINTCOR

SUPREME QUALITY *Since 1986*

USHEVU

Description and Application

NOTE: Gloves and eye protection must be used when handling Ushevu. Water used to rinse Ushevu may kill plants and grass. Once diluted, Ushevu waste water will biodegrade.

CATEGORY

Mould / Algae treatment

DESCRIPTION

Ushevu is an anti-bacterial surface sterilizer used for killing algae contamination before surface painting.

FEATURES

- It is completely effective at eliminating the growth of bacteria, yeast, fungi and algae which occur on all types of surfaces, especially in high humidity conditions.
- It is cost effective with a high level of reduction: Mix 1L to 19L water.

SURFACE PREPARATION AND APPLICATION

1. Dilute Ushevu 1L with 19 litres of water. Ushevu supplied in 250ml spray bottles is ready for use.
2. Apply Ushevu to all algae or mould affected areas using a broom or brush to scrub the Ushevu onto the affected surface.
3. Leave on the surface for 24 hours.
4. Scrub the surface with fresh water to remove traces of dead algae and Ushevu product. Algae changes from green to a brown red once it has been neutralized.
5. Allow sufficient time to dry.
6. Paint the surface as soon as it is dry.

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

