

PAINTCOR

SUPREME QUALITY *Since 1986*

USHEVU

Technical Specifications

Vehicle Type	N/A
Solvent	Water
Enviro Rating	Poisonous
Dilution / Thinning	Water
Theoretical Spread Rate	20m ² per litre
Apply with	Brush or Roller
Drying time	24 Hours
Wash ability	N/A
Elongation	N/A
Pigment	Non-Pigmented
Solids Volume	5% active after dilution
Flexibility	N/A
Colour	Amber Liquid
Finish	N/A
Storage	Cool, dry place. Keep out of reach of children
Over coating	N/A
Packaging	250ml, 1L and 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	N/A
Resistance to Solvents	N/A
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Poisonous Keep out of reach of children
Catalyst Ratio	N/A
Recommended Dry Film	N/A
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Amber Liquid

Note: See Material Safety or Description & Application Data Sheets for safe handling.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

