

# PAINTCOR

SUPREME QUALITY *Since 1986*

## WOOD1ST

### Technical Specifications

Vehicle Type	Linoleic Rich Flexible Long Oil Alkyds
Solvent	Turpentine
Enviro Rating	Flammable
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	10-15m <sup>2</sup> per litre
Apply with	Brush, Roller or Spray
Drying time	Surface Dry: 1 hour Hard Dry: 6 hours Overcoat : After 12 hours
Wash ability	Excellent
Elongation	Very Good
Pigment	Non Pigmented
Solids Volume	37.5%
Flexibility	Good
Colour	Transparent
Finish	Low Gloss
Storage	Cool, dry place. Keep out of reach of children.
Over coating	WoodLuv and WoodCoat
Packaging	1L and 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Fair
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	± 20 microns per coat Apply at least two coats on soft wood
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Amber coloured varnish (clear)

#### Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
sale@paintcor.co.za  
**Website**  
www.paintcor.co.za

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1565  
+27(0) 84 305 5636



**SABS**  
ISO 9001 Accredited

