

PAINTCOR

SUPREME QUALITY *Since 1986*

WOODCOAT

Description and Application

CATEGORY

Wood Treatment / Wood Paint

DESCRIPTION

A ready for use exterior clear or stained wood varnish exhibiting good long-term flexibility and waterproofing properties. Its main use is for the treatment and protection of exterior wood surfaces. This product can only be used on new wood, wood with no varnish or paint on it or wood where the old varnish has been removed or well sanded.

FEATURES

- WoodCoat has been designed to be very flexible using Linoleic Rich Alkyd Resins which will not get brittle, as most other alkyds do over time.
- WoodCoat has good UV resistance and excellent water resistance and once applied will dry to a smooth, clear gloss finish.
- WoodCoat is available in clear and various stains.

SURFACE PREPARATION AND APPLICATION

1. Sand wood to a clean, smooth finish. Remove sanding dust.
For prolonged longevity apply Paintcor's Wood1st to nourish and protect untreated, exterior wood before application of any varnish. (See WoodFirst Application Data).
2. Apply 2 coats WoodCoat to areas of wood which cannot be reached, (bottom and sides), once installed. Allow 12 hours to dry between coats.
3. Install wood, then apply 2 coats WoodCoat to all exposed wood (tops), which will seal all screw or nail fitment points. Allow 12 hours to dry between coats.

NOTE: For wood to last outside, it is important to feed and seal all areas of wood including fixing points. Old varnish gets very hard after years of exposure. Some varnish will not except new top coats and will need to be removed before application of new varnish. Please call our Technical Department for assistance.

Cleaning Equipment

Clean all equipment with Turpentine immediately after use.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

