

PAINTCOR

SUPREME QUALITY *Since 1986*

WOODCOAT

Technical Specifications

Vehicle Type	Linoleic Rich Flexible Long Oil Alkyds
Solvent	Turpentine
Enviro Rating	Flammable
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	10-15m ² per litre
Apply with	Brush, Roller OR Spray
Drying time	Surface Dry: 1 hour Hard Dry: 6 hours Overcoat : After 12 hours
Wash ability	Excellent
Elongation	Very Good
Pigment	Non Pigmented
Solids Volume	37.5%
Flexibility	Excellent
Colour	Amber Liquid
Finish	N/A
Storage	Cool, dry place. Keep out of reach of children.
Over coating	N/A
Packaging	1L and 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Fair
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	± 20 microns per coat Apply at least two coats, best results achieved with 3 coats
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Amber coloured varnish (clear)

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

