

# PAINTCOR

SUPREME QUALITY *From 2086*

## WOODLUSTA

### Technical Specifications

Vehicle Type	Polyurethane
Solvent	Turpentine
Enviro Rating	Flammable 3
Dilution/Thinning	Supplied ready for use
Theoretical Spread Rate	15m <sup>2</sup> per litre
Apply With	Brush, roller or spray
Drying Time	@25°C: 6 hours. Sand dry.
Washability	Excellent
Elongation	Good
Pigment	Non Pigmented
Viscosity at 25°C	55 to 60 seconds (Ford Cup No. 4)
Solids Volume	N/A
Flexibility	Good
Colour	Can be stained or left clear
Finish	Suede
Storage	Cool, dry place. Keep out of reach of children.
Overcoating	N/A
Packaging	1l and 5l
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Good
Resistance to Solvents	N/A
Specific Gravity	
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	±20 microns per coat. Apply at least two coats.
Freeze Thaw	N/A
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Amber Varnish