

PAINTCOR

SUPREME QUALITY *Since 1986*

WOODLUV

Description and Application

CATEGORY

Wood Treatment

DESCRIPTION

WoodLuv is ready-to-use as an exterior clear or stained wood varnish. It exhibits excellent long-term flexibility, toughness, UV and water resistance due to the careful selection of resins used in the product. It has been formulated to meet the highest quality standards. WoodLuv allows for rich nourishment and contains protection oils and stabilizers which help achieve a tough yet flexible clear film. This allows for the application to most outdoor wood surfaces such as floors, furniture, window frames and doors. This product can only be used on new wood, on wood with no paint, on wood which has been stripped of all existing varnish or the existing varnish has been well sanded (Please see note).

FEATURES

- It is used for the sealing and protection of exterior wood surfaces.
- It prevents any cracking or flaking, therefore no loss of adhesion will occur.
- It has been carefully formulated to accommodate movement in wood.
- UV scattering pigments and UV absorbers are included in the formulation, ensuring a long-lasting, easy to clean product.

SURFACE PREPARATION AND APPLICATION

1. Sand the wood down to a clean, smooth finish. Remove any sanding dust.

APPLICATION METHOD

1. Paintcor's WoodLuv is best used over Paintcor's Wood1st. (See WoodFirst data sheet for application).
2. Apply two coats of Paintcor's WoodLuv to areas of wood which cannot be reached once the wood has been installed, such as the bottom and the sides. Allow 6 hours to dry between coats.
3. Install wood, then apply 2 - 3 coats of PAintcor's WoodLuv to all exposed surface areas which will seal all screw or nail fitment points. Allow 6 hours to dry between coats.

NOTE: For wood to last outside, it is important to feed and seal all areas of the wood, including fixing points. Old varnish gets very hard after years of exposure. Some varnish will not except new top coats and will need to be removed before application of new varnish. Please call our Technical Department for assistance.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited



PAINTCOR

SUPREME QUALITY *Since 1986*

CLEANING EQUIPMENT

Clean all equipment with Turpentine immediately after use.

Paintcor cc

Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

