

PAINTCOR

SUPREME QUALITY *Since 1986*

WOODLUV

Technical Specifications

Vehicle Type	Linoleic Rich Flexible Long Oil Alkyds
Solvent	Turpentine
Enviro Rating	Flammable 3
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	15-20m ² per litre
Apply with	Brush, Roller OR Spray
Drying time	6 hours at 25°C
Wash ability	Excellent
Elongation	Excellent
Pigment	Non Pigmented
Solids Volume	36.2 - 36.5
Flexibility	Excellent
Colour	Can be stained or left clear
Finish	Gloss
Storage	Cool, dry place. Keep out of reach of children.
Over coating	N/A
Packaging	1L and 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable / Fumes (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	20 - 25µm per coat
Freeze Thaw	N/A
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Pale amber varnish

Note: This product must be used in conjunction with Paintcor's WoodFirst.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sale@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 Accredited

